

# Declaration of Performance



sovereign group limited

Vale Street,  
Nelson,  
Lancashire  
BB9 0TA  
UK

16

DoP No: **SGSAED02-16**

*SAPA Building Systems; Internally glazed Double leaf Residential Door set (Open In or Out) fitted with exit panic hardware; intended for use in domestic and commercial refurbishment or new building applications on escape routes.*

## Annex ZA.1 of BS EN 14351-1:2006+A1:2010

- Watertightness: **NPD**
- Dangerous Substances: **None released under normal intended use.**
- Resistance to wind load: **NPD**
- Impact resistance (glazed doors with injury risk only): **NPD**
- Load-bearing capacity of safety devices: **Not fitted**
- Height & width (clear opening): **NPD**
- Ability to release (locked doors on escape routes only): **Emergency exit hardware complies with BS EN 1125 when fitted. (See Note 1)**
- Acoustic performance: **NPD**
- Thermal transmittance:  **$\leq 1.8w/m^2k$**
- Radiation Properties: **NPD**
- Air permeability: **NPD**

### Notes:

(1): Continuous surveillance of Factory Production Control (FPC) in compliance with AVCP System 1 as per Annex ZA.2 of BS EN 14351-1: 2006+A1:2010 by BSI, Notified Body No.086. Report No: 0086-CPR-599613, dated July 2013.

For all other essential characteristics, Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

(2): Thermal Transmittance calculation approved by Exova Warringtonfire, Notified Test Body No. 1104. Report No. WIL328908 dated 3/6/13 & WIL326044 dated 11/2/13.

John Hall

Name (Print)

Signature

Director

Position

Date of issue

04-01-16