

Declaration of Performance



sovereign group limited

Vale Street,
Nelson,
Lancashire
BB9 0TA
UK

16

DoP No: **SGVMW04-16**

VEKA Matrix internally glazed opening Combination Window; intended for use in domestic or commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

- Watertightness: **NPD**
- Dangerous Substances: **None released under normal intended use.**
- Resistance to wind load: **NPD**
- Load-bearing capacity of safety devices: **Pass, 350N when fitted (see note 1).**
- Acoustic performance: **NPD**
- Thermal transmittance: **≤ 1.6W/m²k (see note 2).**
- Radiation Properties: **NPD**
- Air permeability: **NPD**

A factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

Notes:

(1): Load bearing Capacity of Safety devices

Report No: 2370/7933731 dated 27/3/13 – BSI, Notified Body No: 086.

Report No: WIL328901 dated 19/6/2013 – Exova Warringtonfire, Notified Body No: 1104.

Report No: WIL327212 dated 17/6/2013 - Exova Warringtonfire, Notified Body No: 1104.

Report No: EW/10/2939/09197/WEL dated 23/2/10 – Wintech Engineering Ltd, Notified Body No: 1288.

Report No: R11164 dated 14/10/10 – Wintech Engineering Ltd, Notified Body No: 1288.

2): Thermal Transmittance calculation approved by Build Check Ltd, Notified Test Body No. 1806.

Report Ref: CU13238-1, CU13238-2 & CU13238-3, dated 18/6/13

JOHN HALL

Name (Print)

Signature

DIRECTOR

Position

04-01-16

Date of issue