

Declaration of Performance



sovereign group limited

Vale Street,
Nelson,
Lancashire
BB9 0TA
UK

16

DoP No: **SGVMD03-16**

VEKA Matrix; Internally glazed Single leaf Residential Combination Door set (Open In or Out); intended for use in domestic and commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

- Watertightness: **NPD**
- Dangerous Substances: **None released under normal intended use.**
- Resistance to wind load: **NPD**
- Impact Resistance (glazed doors with injury risk only): **NPD**
- Load-bearing capacity of safety devices: **Pass, 350N when fitted (see Note 1).**
- Height & width (clear opening): **NPD**
- Acoustic performance: **NPD**
- Thermal transmittance: **$\leq 1.6W/m^2k$ (see Note 2).**
- Radiation Properties: **NPD**
- Air permeability: **NPD**

A factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

Notes:

(1): Load bearing Capacity of safety devices may be fitted to window element only.
Report No. 2370/7933731/1 of 2 Iss3, Dated 27/3/113 – BSI, Notified Body No. 086
Report No: WIL328901 dated 19/6/2013 – Exova Warringtonfire, Notified Body No: 1104.
Report No: WIL327212 dated 17/6/2013 - Exova Warringtonfire, Notified Body No: 1104.

(2): Thermal Transmittance calculation approved by Build Check Ltd, Notified Test Body No. 1806.
Report Ref: CU13238-7, dated 20/6/13 & CU13238-1, dated 18/6/13.

John Hall

Name (Print)

Signature

Director

Position

04-01-16

Date of issue