



sovereign group
doors



sovereign group
doors

Sovereign Group | Ltd
Vale Street, Nelson, Lancashire
BB9 0TA

T: 01282 618171
F: 01282 440456



**GRP Faced Composite Doors for
Social Housing**

Sovereign GRP Composite Door



- Dedicated to volume manufacture of Composite Doors.
- All doors built to survey not cut to size
- Traditional Rimlatch or Multipoint lock options
- No paint used - truly maintenance free
- Unique patented glazing system makes reglazing easy
- PAS 23 and PAS 24 Tested
- Secured by Design Specification
- Fire doors available
- Side panels available
- Part L and Part M compliant

DOOR LEAF

- GRP-faced composite door leaf of nominal 44mm thickness
- Supplied fully finished with hardware and glazing pre-fitted

Fibreglass facings

- Compression moulded for high-definition panel design
- Grained surface finish thermoset skin which culminates in total stability irrespective of climatic and temperature changes.
- No finishing required
- Scratch resistant, pre-pigmented skins
- GRP skin for high impact resistance
- Low maintenance; wipe down with soft cloth and warm water to clean
- UV stable pre-pigmented colour skins: Grained White, Red, Blue, Green, Black, Rosewood, Light Oak

Sub-frame System

- Composite rails and styles, water resistant, reinforced with engineered timber sub-frame.
- Vertical edges finished with metal face plates.

Core Insulation

- Injected polyurethane foam - 100% CFC free

Glazing System

- Cassette glazing system with grained effect to match skins
- Full perimeter sealed and clipped together, hybrid sealant to the glass and glazing cassette to provide waterproofing and promote high adhesion strength for attack resistance, tested to PAS 024
- Pre-glazed with 24mm thickness double-glazed units to BS EN1279
- Glazed units incorporate laminated and toughened glass to BS 6206
- Low-e glass may be supplied, but is NOT required for compliance with part L1 of the Building Regulations for England & Wales.

DOORSET U-VALUE

- Maximum doorset U-value: 2.0 W/m² K⁻¹ (WITHOUT low-e glazing)

PVC-U OUTER FRAMES

- Veka 70mm outer frame
- Fully reinforced (extrusion to BS 6063 and BS 14741)
- Two weather seals, G-lon and brush seal
- UV stable white through colour
- Add-on and ancillary profiles available
- Kitemark: BS7413 (licence no KM 12895)

- Three sill options: 85mm; 155mm; 180mm
- Three extension options: 15mm; 30mm; 45mm
- Available laminated with decorative foil finish - Rosewood on white to outer face

PVC-U Frame Fittings

- Range of aluminium threshold options in anodised gold or mill finish: compliant with part M of the Building Regulations for England & Wales (subject to installation)

HARDWARE

- Fullex Crimebeater Door Lock
- 2-shootbolts plus centre latch and deadbolt
- 92mm handle centres; 45mm and 35mm backsets
- Euro-profile Anti-Drill cylinder; brass or nickel finish, with cylinder guard.
- 44mm wide full-height "clean" wrap-around faceplate completely encapsulates the door edge with matching hinge stile cover-strip, finished in white
- Lever-lever through or split spindle.

Lever furniture

- Cast aluminium lever furniture anodised gold or satin [silver] finish
- Extended lever handles available

Letterplate

- 12" Letterplate: Integral weather seals, internal brush seal Extruded aluminium sprung internal and external flap; anodised gold or satin [silver], white.

Ancillary Hardware

- Crimebeater 3D adjustable butt hinges, white, brown, gold, silver
- Gold Anodised Urn door knocker (with or without spy viewer) other colours available.
- Separate Door viewer:
- Door chain
- Gold Anodised Numerals

STANDARDS

- PAS 23-1:1999 & PAS 24-1:1999
- General performance requirements & Enhanced security performance requirements for door assemblies
- All doorsets shown available as tested and passed at a UKAS accredited test house to PAS 23-1:1999 and PAS 24-1:1999
- Copies of test reports available on request
- Must be supplied to specification as tested
- Fully assembled doorsets must be supplied

Secured by Design

- All doorsets shown available as Secured by Design licensed products
- Specification as per PAS 23-1:1999 and PAS 24-1:1999 with additional security:

ALL DOORS:

- One pane of the double glazed unit Laminated
- Locking cylinder to BS EN 1303 - Grade 3, with anti-pick and anti-drill
- 3-point locking

FRONT DOORS ONLY:

- Door viewer 1500mm standard position, variable upon written request
- Door chain fitted



Sovereign HD30 Fire Rated GRP Composite Door

Specification

- ECO FRAME 44 FIRE RATED 70mm outer frame. UV Stable GRP pre-pigmented colour skins
- Grained in a choice of white, red, blue, black, rosewood, light oak.
- Glazed units to incorporate 6mm Georgian Wire Safety Polished Plate and toughened glazing to BS6206.
- Range of Aluminium threshold options in anodised gold or mill finish, part M compliant
- Winkhaus AV2 Door Lock & Door chain
- 2 Shootbolts plus centre latch and hookbolt
- Winkhaus GTV High Security anti-manipulation cylinder "Anti-Bump Lock"



- Hoppe High Security Lever-lever through or split handle, including cylinder guard.
- Briton Overhead Door Closer
- Cast Aluminium lever furniture anodised gold or satin (silver) finish
- 12" Fire Rated Letterplate
- 4 Nr Winkhaus ECO Stainless Steel Frame Door Hinges
- Gold anodised Urn door knocker (with or without spy viewer)
- Gold anodised numerals

Secured by Design



Official Police Security Initiative