Declaration of Performance





Vale Street, Nelson, Lancashire BB9 0TA UK

16

DoP No: SGSAW01-16

SAPA Building Systems internally glazed opening Casement Window; intended for use in domestic or commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

- Watertightness: NPD
- Dangerous Substances: None released under normal intended use.
- Resistance to wind load: NPD
- Load-bearing capacity of safety devices: Pass, 350N when fitted (see note 1).
- Acoustic performance: NPD
- Thermal transmittance: ≤ 1.6W/m²k (see note 2).
- · Radiation Properties: NPD
- Air permeability: NPD

A factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

Notes:

(1): Load bearing Capacity of Safety devices

Report No: WIL331894 dated 25/9/13, Exova Warringtonfire, Notified Test Body No. 1104. Report No: WIL330315 dated 26/7/13, Exova Warringtonfire, Notified Test Body No. 1104. Report No: EW/10/2940/WEL dated 23/2/10 – Wintech Engineering Ltd, Notified Body No: 1288.

(2): Thermal Transmittance calculation approved by Exova Warringtonfire, Notified Test Body No. 1104. Report No: WIL328908 dated 3/6/13 & WIL326044 dated 11/2/13.

TOHO HALL Name (Print)	Signature Signature
DIRACSON	04-01-16
Position	Date of issue