Declaration of Performance





Vale Street, Nelson, Lancashire BB9 0TA UK

16

DoP No: SGVMD04-16

VEKA Matrix; Internally glazed Sliding Patio (In-line or Tilt & Slide) Residential Door set (Open In or Out); intended for use in domestic and commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

- Watertightness: NPD
- Dangerous Substances: None released under normal intended use.
- Resistance to wind load: NPD
- Impact Resistance (glazed doors with injury risk only): NPD
- · Load-bearing capacity of safety devices: Not fitted
- · Height & width (clear opening): NPD
- Acoustic performance: NPD
- Thermal transmittance: ≤ 1.6W/m²k (see Note 1).
- Radiation Properties: NPD
- Air permeability: NPD

A factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

Notes:

(1): Thermal Transmittance calculation approved by Build Check Ltd, Notified Test Body No. 1806. Report Ref: CU13238-8, dated 20/6/13 & CU13238-5, dated 20/6/13.

Name (Print)	Signature Shared.
DIRRESON	04-01-16 Date of issue