## **Declaration of Performance**





Vale Street, Nelson, Lancashire BB9 OTA UK

16

DoP No: SGVMW02-16

VEKA Matrix internally glazed opening Tilt & Turn Window; intended for use in domestic or commercial refurbishment or new building applications.

## Annex ZA.1 of BS EN 14351-1:2006+A1:2010

- Watertightness: NPD
- Dangerous Substances: None released under normal intended use.
- Resistance to wind load: NPD
- Load-bearing capacity of safety devices: Pass, 350N when fitted (see note 1).
- Acoustic performance: NPD
- Thermal transmittance: ≤ 1.6W/m²k (see note 2).
- Radiation Properties: NPD
- Air permeability: NPD

A factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

## Notes

(1) Load bearing Capacity of Safety devices

Report No: WIL328901 dated 19/6/2013 - Exova Warringtonfire, Notified Body No: 1104.

2): Thermal Transmittance calculation approved by Build Check Ltd, Notified Test Body No. 1806. Report Ref: CU13238-3, dated 18/6/13

Name (Print)

Signature

Of Of M

1) RACTOR Position O4-01-16 Date of issue